




## Great Range Bearing Supplier

### 6900 NTN New Single Row Ball Bearing



Bearing No. 6900

Size	10x22x6 mm
Bore Diameter	10 mm
Outer Diameter	22 mm
Width	6 mm
d	10 mm
D	22 mm
B	6 mm
C	6 mm
r min.	0,3 mm
da min.	12 mm
da max	13 mm
Da max.	20 mm
ra max.	0,3 mm
Weight	0,009 Kg
Basic dynamic load rating (C)	2,7 kN
Basic static load rating (C0)	1,27 kN
(Grease) Lubrication Speed	30 000 r/min
(Oil) Lubrication Speed	36 000 r/min
rs min	0.3 mm
Radial clearance class	CN
Mass	0.009 kg
Dynamic load, C	2.7 kN
Static load, C0	1.27 kN
Fatigue limit load, Cu	0.06 kN
f0	14
Nlim (oil)	36,000 rpm

6900 Bearing 2D drawings and 3D CAD models



## Great Range Bearing Supplier

Nlim (grease)	30,000 rpm
Min operating temperature, Tmin	-20 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.84 Hz
Characteristic outer ring frequency, BPF0	3.61 Hz
Characteristic inner ring frequency, BRF1	5.39 Hz
da min	12 mm
Da max	20 mm
ra max	0.3 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.009
EAN	4547359006476
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	10MM Bore; 22MM



## Great Range Bearing Supplier

	Outside Diameter; 6MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	6900
Weight / LBS	0.02
Outer Race Width	0.236 Inch   6 Millimeter
Bore	0.394 Inch   10 Millimeter
Outside Diameter	0.866 Inch   22 Millimeter
bore diameter:	10 mm
finish/coating:	Uncoated
outside diameter:	22 mm
bearing material:	High Carbon Chrome Steel
overall width:	6 mm
cage material:	Steel
bore type:	Round
inner ring width:	6 mm
closure type:	Open
outer ring width:	6 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	30000 rpm
snap ring included:	Without Snap Ring
maximum rpm (oil):	36000 rpm
internal clearance:	CN
fillet radius:	0.3 mm



## Great Range Bearing Supplier

operating temperature range:	-40 to 120 ° C
maximum rpm:	36000 RPM
dynamic load capacity:	2700 N
series:	69
static load capacity:	1270 N
manufacturer product page:	<a href="#">Click here</a>
precision rating:	Class 0